













3/2		Solenoid - Spring		Ordering code		Solenoid - Spring		5/2	
   Weight gr. 80 Minimum working pressure 2 bar				805. T .0.1. V		   Weight gr. 85 Minimum working pressure 2 bar			
				TYPE T32 = 3 ways 52 = 5 ways VOLTAGE 01 = 12V D.C. 02 = 24V D.C. 05 = 24V A.C. 06 = 110V A.C. 07 = 220V A.C.					
Operational characteristic		Fluid	Max working pressure (bar)	Temperature °C		Flow rate at 6 bar with Δp=1 (Nl/min)	Orifice size (mm)	Working ports size	
		Filtered and lubricated air	10 bar	Min. -5°C Max. +50°C	160 Nl/min	mm 2,5	M5		

3/2		Solenoid - Differential		Ordering code		Solenoid - Differential		5/2	
   Weight gr. 85 Minimum working pressure 2 bar				805. T .0.12. V		   Weight gr. 90 Minimum working pressure 2 bar			
				TYPE T32 = 3 ways 52 = 5 ways VOLTAGE 01 = 12V D.C. 02 = 24V D.C. 05 = 24V A.C. 06 = 110V A.C. 07 = 220V A.C.					
Operational characteristic		Fluid	Max working pressure (bar)	Temperature °C		Flow rate at 6 bar with Δp=1 (Nl/min)	Orifice size (mm)	Working ports size	
		Filtered and lubricated air	10 bar	Min. -5°C Max. +50°C	160 Nl/min	mm 2,5	M5		

3/2		Solenoid - Solenoid		Ordering code		Solenoid - Solenoid		5/2	
   Weight gr. 120 Minimum working pressure 1,5 bar				805. T .0.0. V		   Weight gr. 125 Minimum working pressure 1,5 bar			
				TYPE T32 = 3 ways 52 = 5 ways VOLTAGE 01 = 12V D.C. 02 = 24V D.C. 05 = 24V A.C. 06 = 110V A.C. 07 = 220V A.C.					
Operational characteristic		Fluid	Max working pressure (bar)	Temperature °C		Flow rate at 6 bar with Δp=1 (Nl/min)	Orifice size (mm)	Working ports size	
		Filtered and lubricated air	10 bar	Min. -5°C Max. +50°C	160 Nl/min	mm 2,5	M5		

